

FlexVIEW™ II

LED Displays



Features & Benefits

- 11-color ultra-bright LED technology
- 160° viewing angle and anti-glare filter for optimum visibility
- Integrated Ethernet (TCP/IP) connectivity using standard CAT 5 wiring and optional wireless capability
- Optional serial connectivity
- Supports variable font sizes from 1.5" (3.8cm) to 6" (15cm)
- Provides multiple scrolling effects
- Low cost of ownership



Delivering Business Communication Vitals

www.txdigital.com

sales@txdigital.com

Toll Free (North America): 800.693.2628

Outside North America: +1.979.693.9378

Fax: 979.694.2402

400 Technology Parkway
College Station, TX 77845

Texas Digital, QuickCOM, FlexVIEW, FlexVIEW Lite, FlexVIEW II, VitalCAST and VitalCAST Content Manager are trademarks of Texas Digital Systems, Inc. All other trademarks are the property of their respective owners. © 2010, Texas Digital Systems, Inc. 1107

Deliver real-time data with a value-based display

FlexVIEW II displays are the next generation of our FlexVIEW line. The FlexVIEW II line of displays are high performance, network-connected, full-matrix LED displays that deliver increased communication speed, higher bandwidth and improved connectivity. FlexVIEW displays connect using standard Cat 5 wiring.



With a variety of models available to meet the different needs of contact centers, help desks and command centers, FlexVIEW II LED displays enable you to respond faster to critical events, improve productivity levels and communicate business vitals in real time.

Integrated with Texas Digital's QuickCOM Enterprise™ real-time messaging and alert communication solution, FlexVIEW II displays visually deliver real-time, critical system status information from ACD systems, help desk packages, mainframes, automation packages, network-monitoring packages, ODBC databases and serial data sources to minimize response time and maximize team effort.

Model	Size (pixels)	Dimensions (w x h x d)	Weight	# of Lines	Power
113	7 x 80	26" x 4" x 2" 66 x 10 x 5 cm	3.5 lbs 1.6 kg	1	110/220 VAC
120	7 x 120	38" x 4" x 2" 97 x 10 x 5 cm	5.4 lbs 2.5 kg	1	110/220 VAC
126	7 x 160	50" x 4" x 2" 127 x 10 x 5 cm	7.1 lbs 3.2 kg	1	110/220 VAC
133	7 x 200	62" x 4" x 2" 158 x 10 x 5 cm	9.1 lbs 4.2 kg	1	110/220 VAC
221	16 x 128	41" x 6" x 3.2" 104 x 15.3 x 8.4 cm	11.2 lbs 5.1 kg	2	110/220 VAC
232	16 x 192	60" x 6" x 3.2" 153 x 15.3 x 8.4 cm	16.2 lbs 7.4 kg	2	110/220 VAC
321	24x128	41.8" x 10.5" x 3.5" 105.6 x 26.3 x 8.5 cm	26 lbs 11.8 kg	3	110/220 VAC
332	24x192	61.5" x 10.5" x 3.5" 154.4 x 26.3 x 8.5 cm	32 lbs 14.8 kg	3	110/220 VAC
342	24x256	80.2" x 10.5" x 3.5" 203.7 x 26.3 x 8.5 cm	36 lbs 16.3 kg	3	110/220 VAC
432	32x192	61.5" x 12.2" x 4.4" 154.4 x 31 x 11 cm	36 lbs 16.3 kg	4	110/220 VAC
821	64 x 128	42.4" x 23.2" x 5" 107.7 x 58.9 x 12.7 cm	55 lbs 24.9 kg	8	110/220 VAC
842	64 x 256	80.8" x 23.2" x 5" 205.2 x 58.9 x 12.7	105 lbs 47.6 kg	8	110/220 VAC