

CineVIEW LED Cinema Signage



Benefits

- Updates information in real time and saves valuable time and labor costs
- Ease of use with direct interface to ticketing system
- Displays show schedule and screen locations
- Improves image perception
- Branding opportunities

Features

- 1.25" or 2.1" character sizes
- Choice of red, amber or alternating red/amber lines
- Serial and Ethernet TCP/IP connectivity
- Little or no maintenance
- 160° viewing angle
- Scrolling text available

Brilliant solutions that make your theatre shine

Enhance the movie-going experience with Texas Digital's CineVIEW indoor LED displays that deliver information in a colorful, professional and impressive format.

Texas Digital's wide range of indoor LEDs (light emitting diode) show current information in real-time with a direct interface to your theatre's point-of-sale ticketing



Auditorium displays clearly identify each show

system. CineVIEW displays are low-maintenance, requiring little updating effort compared to the labor-intensive updates of outdated Mylar®, letter-boards and static graphics.



Lobby Displays direct movie-goers to their auditorium

Box Office displays show movie titles, ratings and show times for customers to view while purchasing their tickets. With the added flexibility of showing current concessions and special promotions with easy-to-read messages, you can increase sales and drive profitability.



CineVIEW directly interfaces with your POS system for real time updates



Texas Digital™

Delivering Business Communication Vitals

⌘ CineVIEW Technical Specifications

Physical Specifications	
Pixel Colors:	Hi-bright red and amber with wide viewing angle.
Character Set:	Upper/lower case ASCII with international characters.
Visibility:	Optimal spacing provides greater viewing distances and better character definition.
Fascia:	A special, high quality matte poly-carbonate finish reduces glare, enhances contrast and improves overall visibility.
Mounting:	Ceiling or wall mount options available.
Communication Options:	RS232C Serial Port RS485 Multi-Drop Serial Port (user-selectable display address) Ethernet 10-Base-T

Services	
Warranty:	All displays are covered under Texas Digital's warranty plan.
Product Testing:	Texas Digital's displays are subjected to rigorous inspection and testing to ensure optimal operation and functionality.
Direct Service Network:	Texas Digital provides comprehensive on-site maintenance and assembly replacement nationwide.
Customer Support:	Our national Customer Support Center provides quick and efficient problem resolution.
Strategic Partners:	Texas Digital partners with leading ticketing software providers, component suppliers, systems integrators and distributors to deliver the absolute best in innovation and reliability.

LED Display Measurements

Box Office Display		Lobby Display		Side by Side
	48 Character Width	60 Character Width		24 Character Width
			4 Lines	13.25"h x 47"w x 4"d
6 Lines	14.90"h x 56.85"w x 3.50"d	14.90"h x 70.05"w x 3.50"d	6 Lines	18"h x 47"w x 4"d
8 Lines	18.50"h x 56.85"w x 3.50"d	18.50"h x 70.05"w x 3.50"d	8 Lines	22.75"h x 47"w x 4"d
10 Lines	22.10"h x 56.85"w x 3.50"d	22.10"h x 70.05"w x 3.50"d	10 Lines	27"h x 47"w x 4"d
12 Lines	25.7"h x 56.85"w x 3.50"d	25.70"h x 70.05"w x 3.50"d	12 Lines	31.75"h x 47"w x 4"d
14 & 16 Lines	* available upon request *		14 & 16 Lines	* available upon request *

Both the **Box Office and Lobby Displays** are also available in a **side by side format**. To calculate these measurements, **double the width**, the height and depth will be the same according to the number of lines and display type.

Auditorium Display		
	20 Character Width	24 Character Width
1 Line	4"h x 38.25"w x 2"d	3.75"h x 44.25"w x 2.75"d

Power/Environment Requirements

Box Office Display		Lobby/Auditorium Display	
Input:	AC 100V to 254V at 47 ~ 63 Hz	Input:	AC 100V to 254V at 47 ~ 63 Hz
Power Consumption:	Varies by size: 1200 watt maximum	Power Consumption:	500 watt maximum
Operating Temp:	0° to 50° Celsius or 32° to 122° Fahrenheit	Operating Temp:	0° to 50° Celsius or 32° to 122° Fahrenheit
Humidity Range:	0 to 95% non-condensing	Humidity Range:	0 to 95% non-condensing

LED Display Details

Box Office Display		Lobby/Auditorium Display	
Pixel Spacing:	0.18" apart	Pixel Spacing:	0.3" apart
Character Sizes:	1.25" height characters in single color full matrix 2 x 12 LED modules for ease of servicing	Character Sizes:	2.1" height characters in single color full matrix LED modules (12 characters wide)



Delivering Business Communication Vitals

www.txdigital.com • cinemasales@txdigital.com

Toll Free (North America): 800.693.2628

Outside North America: +1.979.693.9378

Fax: 979.694.2402

400 Technology Parkway • College Station, TX 77845

Texas Digital and Cinema Display Units are trademarks of Texas Digital Systems, Inc. All other trademarks are the property of their respective owners. © 2006, Texas Digital Systems, Inc. · 07/06