

# ⚡ VitalCAST Technical Specifications

A complete VitalCAST system includes all media player PC hardware and peripherals, LCD/plasma displays, software licenses, training and support.

## Indoor Displays

\*Other displays are also available if different specifications are required.\*

	20" LCD	32" LCD	37" LCD	42" LCD	42" plasma
Resolution:	640 x 480 p	1366 x 768 p	1366 x 768 p	1366 x 768 p	1024 x 768 p
Brightness:	500 Nits	550 Nits	600 Nits	600 Nits	1500 Nits
Color Depth:	24 bit	24 bit	24 bit	24 bit	24 bit

## Mechanical Requirements

	20" LCD	32" LCD	37" LCD	42" LCD	42" plasma
Height:	18.13"h	19.41"h	22.49"h	25.71"h	25.58"h
Width:	23.52"w	31.61"w	36.54"w	41.61"w	41.97"w
Depth:	8.74"d	3.93"d	4.43"d	4.41"d	3.84"d
Weight:	16.26 lbs.	36.46 lbs.	55.13 lbs.	79.2 lbs.	65 lbs.
Mounting Plate:	VESA Standard Mount Interface	VESA Standard or Wall Mount RW200	Wall Mount RW300	Wall Mount RW300	Wall Mount PWMT200

## Power / Environmental Requirements

All displays have the necessary UL, cUL (Canadian) and FCC regulatory certifications.

	20" LCD	32" LCD	37" LCD	42" LCD	42" plasma
Power Source:	100 ~240 VAC, 50/60 Hz 1 A	90~264 VAC, 47/63 Hz 3.6 A	90~264 VAC, 47/63 Hz 3.6 A	90~264 VAC, 47/63 Hz 3.6 A	115 VAC, 60 Hz 2.2 A
Environment:	50° F to 95° F < 80% humidity	50° F to 95° F < 80% humidity	50° F to 95° F < 80% humidity	50° F to 95° F < 80% humidity	32° F to 104° F < 80% humidity

\*Note: Specifications subject to change.\*

For more information on how digital signage can improve & enhance your business, contact Texas Digital at (800) 693-2628 or (979) 693-9378 or visit [www.txdigital.com](http://www.txdigital.com).

